

Clipper® Roller Lacer®



CH210



The portable, easy-to-use Clipper® Roller Lacer® makes it easy to lace belts up to 60" (1500 mm) wide in a single operation. Belts wider than the lacer's width can be laced in multiple passes with the continuous lacing feature. A handle-actuated belt clamp holds belts securely while twin rollers embed fasteners evenly to create a strong, long-lasting splice.

Market applications

- Parcel services
- General material handling
- Corrugated box board
- Food processing
- Distribution centers
- Ag/Combine pick-up belts

A durable, lightweight body made from sturdy aircraft aluminum and a carrying handle make it easy to take the Roller Lacer on-site to lace belts right on the conveyor. Plus, there is room for extra lacer pins and face strips in a handy storage compartment.

For more frequent lacing applications, and/or when installing hooks into hard belts, specify the Roller Lacer with the optional steel lacing head.



Clipper®

Clipper® Roller Lacer®



Roller Lacer®

Does not include face strips – purchase separately.

Lacer Width		Ordering Number	
in.	mm	Standard Lacer	Steel Head Lacer
24	600	RL-24	SHRL-24
36	900	RL-36	SHRL-36
48	1200	RL-48	SHRL-48
60	1500	RL-60	SHRL-60

Roller Lacer® Face Strips

Includes one lacer pin.

Belt Width		Ordering Number
in.	mm	
For Hook Size: 30		
24	600	GFS30-24
36	900	GFS30-36
48	1200	GFS30-48
60	1500	GFS30-60
For Hook Size: 36, UCM36		
24	600	FS36-24
36	900	FS36-36
48	1200	FS36-48
60	1500	FS36-60
For Hook Size: 1, UX-1		
24	600	FS1-24
36	900	FS1-36
48	1200	FS1-48
60	1500	FS1-60
For Hook Size: 2-4, U2SP-U3		
24	600	FS2-24
36	900	FS2-36
48	1200	FS2-48
60	1500	FS2-60
For Hook Size: 4-1/2-7, U4-U7		
24	600	FS4-1/2-24
36	900	FS4-1/2-36
48	1200	FS4-1/2-48
60	1500	FS4-1/2-60



Eng-Thira Co., Ltd.
1721/5 Chan Road
Kwang Thungmahamek, Khet Sathorn
Bangkok 10120, Thailand
Tel: 01-816-4445

